



L&T MARKETING SDN BHD



*Robina*<sup>®</sup>

# Robina Flooring - Floor Preparation & Site Condition Requirements

It is very important that users or contractors to follow the floor preparation and site condition requirements to ensure an excellent installation thus finishes.

## I) Installation Method

The method of installation is “floating system” and shall be accordance to manufacturer’s recommendation. Changes in designs, patterns motifs, borders or similar will be charged separately.

## II) Surface or Sub-floor Requirements

- a) Floor surface must be clean from any debris, dry and even. The level shall be within a tolerance of +/- 3mm within an area of one square meter and preferred to be smooth screed. Rectification work will be charged separately as variation order.
- b) All wall edges when plastering shall be of right angles to avoid skirting gaps. Filling up of gaps will be considered as variation order and subject to additional charges.
- c) Staircase treads, riser and landing to form at right angles, same width, height and parallel alignment.
- d) All newly cement screed floor must have at least 60 days curing time prior to the installation of our flooring system.
- e) Ground floor or basement area must be water proofed prior to the installation of our flooring system.

## III) Other Requirements

- a) Sanitary fittings, window & electrical fitting, painting & wet works and other trades that might result in the damages of flooring shall be commenced and completed prior to the installation of our flooring system.
- b) Door clearance shall be of minimum 20mm from screed floor.
- c) Contractor or buyer to confirm that all necessary water feature fittings are properly installed and there must not have any water leakage.
- d) Contractor or buyer to provide electricity and water supply, hoisting facility and other facilities deemed fit for the progress of work.
- e) Storage area to be provided at site to prevent damages or mishandling.

Note : Due to the principle of floating installation method, it is prohibited to affix any fixtures or fitting onto the sub-floor that would deter the required expansion.